




## Olhais de Suspensão Forjados

### DIN 580 Material C 15



Refª	Dimensões (mm)								S.W.L. (kg)		Peso (kg)	Código
	A	B	C	E	F	G	H	L	Vertical	45°		
M 6	20	36	20	6	8	10	36	13	90	60	0,060	309.00006
M 8	20	36	20	6	8	10	36	13	140	95	0,060	309.00008
M 10	25	45	25	8	10	12	45	17	230	170	0,110	309.00010
M 12	30	54	30	10	12	14	53	20,5	340	240	0,170	309.00012
M 14	30	54	30	10	12	14	53	20,5	600	400	0,170	309.00014
M 16	35	63	35	12	14	16	62	27	700	500	0,310	309.00016
M 18	35	63	35	12	14	16	62	27	930	650	0,480	309.00018
M 20	40	72	40	14	16	19	71	30	1200	830	0,480	309.00020
M 22	40	72	40	14	16	19	71	30	1500	1000	0,480	309.00022
M 24	50	90	50	18	20	24	90	36	1800	1270	0,900	309.00024
M 27	54	98	62	20	22	26	99	40	2500	2300	1,250	309.00027
M 30	60	108	65	22	24	28	109	45	3600	2600	1,700	309.00030
M 36	70	126	75	26	28	32	128	54	5100	3700	2,150	309.00036
M 42	80	144	85	30	32	38	147	63	7000	5000	4,150	309.00042

### DIN 582 Material C 15



Refª	Dimensões (mm)								S.W.L. (kg)		Peso (kg)	Código
	A	B	C	E	F	G	H	Vertical	45°			
M 8	20	36	20	8,5	8	10	36	140	95	0,06	309.01008	
M 10	25	45	25	10	10	12	45	230	170	0,10	309.01010	
M 12	30	54	30	11	12	14	53	340	240	0,17	309.01012	
M 16	35	63	35	13	14	16	62	700	500	0,26	309.01016	
M 20	40	72	40	16	16	19	71	1200	830	0,41	309.01020	
M 24	50	90	50	20	20	24	90	1800	1270	0,75	309.01024	